



COMMERCIAL SLICER GL-300

Blade Ø 300 mm.



DYNAMIC PREPARATION
GEAR DRIVEN SLICERS



SALES DESCRIPTION

Gear driven slicer.

Gear driven commercial slicer with ring, carriage lock and blade removal tool.

- ✓ Slicer Fully made of high-polished aluminium protected against anodic oxidation.
- ✓ Built-in precision sharpener.
- ✓ Hard-chromed forged scoop knife.
- ✓ Life-lubricated helicoidal gear drive.
- ✓ Easy selection of cutting thickness.
- ✓ Bearing-mounted slide plate.
- ✓ Professional slicer with ring, carriage lock and blade removal tool.
- ✓ Heavy duty, ventilated motor.

Components in contact with food are completely detachable for easier cleaning.

SPECIFICATIONS

Blade diameter: 300 mm

Cutting capacity

- ✓ Square cut: 210 mm x 210 mm
- ✓ Round cut: 210 mm
- ✓ Rectangular cut: 210 mm x 270 mm

Slice thickness: 0 mm - 15 mm

Carriage run: 320 mm

Total loading: 430 W

IP Protection grade: 43

External dimensions (WxDxH)

- ✓ Width: 800 mm
- ✓ Depth: 560 mm
- ✓ Height: 460 mm

Net weight: 38 Kg

Noise level (1m.): 65 dB(A)

Crated dimensions

840 x 630 x 650 mm

Gross weight: 57 Kg

AVAILABLE MODELS

5050062 Slicer GL-300 230-400/50/3

5050067 Slicer GL-300 120/60/1

5050068 Slicer GL-300 230/50/1

5050069 Slicer GL-300 220/60/1

* Ask for special versions availability



sammic | www.sammic.com
Food Service Equipment Manufacturer

Polígono Basarte, 1.
20720 Azkoitia, Spain

phone +34 943 15 72 36
sales@sammic.com



Project

Date

Item

Qty

Approved

product sheet
updated 13/07/2022