RACK CONVEYOR DISHWASHER SRC-2200

85 / 126 baskets per hour (up to 2200 plates/hour). Washing + rinsing.

Sales Description

2 speeds.

- ✓ Fully stainless steel jacket.
- ✓ Inlet and outlet splash guards are standard.
- ✓ Stainless steel central rack feed system.
- ✓ Process cycles are divided by rubber curtains.
- ✓ Automatic cycle start.

Economy

- ✓ Energy saving rinse supply switch.
- ✓ Pressure controller in the rinse section to limit consumption.
- ✓ Programmed automatic stops if there is no loading.
- ✓ Stop and freezing of timer when the limit switch actuates.

Cleaning and maintenance

- ✓ Wide pivoting door allowing access for cleaning or inspection purpose.
- ✓ Detachable arms and dispersers for easier cleaning.
- ✓ Sloped removable stainless steel filters with independent removable basket.
- ✓ Easy boiler emptying by loosening a hose.
- ✓ Failures are easily detected thanks to the warning lights.
- ✓ Easy to repair without moving the machine.

Washing

- ✓ Stainless steel wash arms and deep-drawn dispersers.
- ✓ Efficient and durable wash arm dispersers.
- ✓ Powerful, self-draining vertical wash pump.
- ✓ Easy to install detergent dispenser intake in washing tank. Rinsing

Rinsing

- ✓ Stainless steel rinse arms and powerful, stainless steel, deep-drawn dispersers.
- ✓ Automatic boiler filling with no failure risk for heating elements.
- ✓ Temperature control with high precision probes.
- ✓ Visualisation and adjustment of washing and rinsing temperatures in the digital display by pressing a button.
- ✓ Easy to install rinse aid dispenser intake in boiler.

Includes

- ✓ Inlet and outlet splash guards are standard.
- ✓ Extraction hood without motor CA.
- ✓ 3 mixed baskets (plates).

Optional

- ❑ Drying unit TS-600 / TS-90.
- ❑ Extraction hood with motor EV.
- ❑ Extraction hood with steam condensation CV.
- ❑ Inlet tables and compositions.
- ❑ Outlet tables and compositions.

Accessories

- ❑ Manual water softeners
- ❑ Automatic water softeners
- ❑ 500 x 500 mm baskets
- ❑ Inserts & supplements
- ❑ Loading table for corner situation for rack conveyor dishwashers
- ❑ Central sorting tables
- ❑ Double connection central sorting table
- ❑ Single exit tables
- ❑ Roller conveyor and corner roller conveyor (exit)
- ❑ Machined curve (exit)
- ❑ Connecting tables for pass-through dishwashers and rack conveyors

Specifications

Basket dimensions: 500 x 500 mm
Useful height: 400 mm

Production

- ✓ Production baskets/hour: 85 / 126
- ✓ Production plates/hour: 1530 / 2200

Wash

- ✓ Temperature: 55ºC - 65ºC
- ✓ Wash tank capacity: 100 l
- ✓ Pump: 3 Hp / 2250 W
- ✓ Wash heating element: 9000 W

Rinse

- ✓ Temperature: 80ºC - 90ºC
- ✓ Water consumption: 300 l/h
- ✓ Rinse heating element: 18000 W
- ✓ Boiler capacity: 20 l

Drag

- ✓ Drag motor power: 0.25 Hp / 180 W

Loading

- ✓ Central module total power: 29580 W

External dimensions (W x D x H)

- ✓ Width: 1700 mm
- ✓ Depth: 829 mm
- ✓ Height: 1520 mm

Net weight: 250 kg

Water Intake: 3/4”
Drain diameter: 1 1/2”
Noise level (1m.): 71 dB(A)

SAMMIC, S.L.
Basarte, 1 · 20720 AZKOITIA
www.sammic.com

product sheet
updated 14/02/2024

Copyright 2024 © Sammic S.L.

RACK CONVEYOR DISHWASHER SRC-2200

85 / 126 baskets per hour (up to 2200 plates/hour). Washing + rinsing.

WARE WASHING
RACK CONVEYOR DISHWASHERS

Electrical supply:

- ✓ 400V / 50 Hz / 3N
- ✓ 220V / 60 Hz / 3
- ✓ 440V / 60 Hz / 3

Please note: +3kW rinse heating element in models equipped with steam condenser.

Available Models

1302507	SRC-2200DCA 400/50/3N
1302526	SRC-2200DCA 220/60/3
1302510	SRC-2200DEV 400/50/3N
1302503	SRC-2200DCV 400/50/3N
1302508	SRC-2200DS6CA 400/50/3N
1302529	SRC-2200DS6CA 400/50/3N
1302511	SRC-2200DS6EV 400/50/3N
1302504	SRC-2200DS6CV 400/50/3N
1302509	SRC-2200DS90CA 400/50/3N
1302512	SRC-2200DS90EV 400/50/3N
1302506	SRC-2200DS90CV 400/50/3N
1302519	SRC-2200ICA 400/50/3N
1302528	SRC-2200ICA 220/60/3
1302522	SRC-2200IEV 400/50/3N
1302516	SRC-2200ICV 400/50/3N
1302520	SRC-2200IS6CA 400/50/3N
1302525	SRC-2200IS6CA 220/60/3
1302527	SRC-2200IS6CA 220/50/3
1302523	SRC-2200IS6EV 400/50/3N
1302515	SRC-2200IS6CV 400/50/3N
1302521	SRC-2200IS90CA 400/50/3N
1302524	SRC-2200IS90EV 400/50/3N
1302518	SRC-2200IS90CV 400/50/3N

** Ask for special versions availability*

sammic | www.sammic.com
Food Service Equiment Manufacturer
Polígono Basarte, 1.
20720 Azkoitia, Spain
phone +34 943 15 72 36
sales@sammic.com

Project	Date
Item	Qty
Approved	

product sheet
updated **14/02/2024**

Copyright 2024 © Sammic S.L.