RACK CONVEYOR DISHWASHER SRC-5000



183 / 275 baskets per hour (up to 4950 plates/hour). Pre-washing + first washing + enhanced washing + double rinsing.



SALES DESCRIPTION

2 speeds.

- √ Fully stainless steel jacket.
- √ Inlet and outlet splash guards are standard.
- √ Stainless steel central rack feed system.
- ✓ Process cycles are divided by rubber curtains.
- ✓ Automatic cycle start.

Economy

- ✓ Energy saving rinse supply switch.
- ✓ Pressure controller in the rinse section to limit consumption.
- Programmed automatic stops if there is no loading.
- √ Stop and freezing of timer when the limit switch actuates.

Cleaning and maintenance

- √ Wide pivoting door allowing access for cleaning or inspection purpose.
- Detachable arms and dispersers for easier cleaning.
- ✓ Sloped removable stainless steel filters with independent removable basket.
- √ Easy boiler emptying by loosening a hose.
- √ Failures are easily detected thanks to the warning lights.
- √ Easy to repair without moving the machine.

Washing

- √ Stainless steel wash arms and deep-drawn dispersers.
- Efficient and durable wash arm dispersers.
- ✓ Powerful, self-draining vertical wash pump.
- ✓ Easy to install detergent dispenser intake in washing tank. Rinsing

Rinsing

- Stainless steel rinse arms and powerful, stainless steel, deep-drawn
- Automatic boiler filling with no failure risk for heating elements.







- Temperature control with high precision probes.
- √ Visualisation and adjustment of washing and rinsing temperatures in the digital display by pressing a button.
- Easy to install rinse aid dispenser intake in boiler.

NCLUDES

- Inlet and outlet splash guards are standard.
- Extraction hood without motor
- CA.
- 3 mixed baskets (plates).

OPTIONAL

- □ Drying unit TS-800 / TS-90.
- Extraction hood with motor EV.
- Extraction hood with steam condensation CV.
- ☐ Inlet tables and compositions.
- Outlet tables and compositions.

Accessories

- Manual water softeners
- Automatic water softeners
- □ 500 x 500 mm baskets
- ☐ Inserts & supplements
- Loading table for corner situation for rack conveyor dishwashers
- Central sorting tables
- Double connection central sorting table
- Single exit tables
- ☐ Roller conveyor and corner roller conveyor (exit)
- Machined curve (exit)
- Connecting tables for pass-through dishwashers and rack conveyors

SPECIFICATIONS

Basket dimensions: 500 x 500 mm Useful height: 400 mm

Production

- ✓ Production baskets/hour: 183 / 275
- ✓ Production plates/hour: 3294 / 4950

Pre-wash

- ✓ Temperature: 35°C 45°C
- ✓ Pre-wash basin capacity: 60 I
- ✓ Pump: 1.2 Hp / 880 W

First wash

- ✓ Temperature: 55°C 65°C
- √ 1st wash tank capacity: 60 I
- ✓ Pump: 1.2 Hp / 880 W
- √ 1st wash heating element: 6000 W

Boosted wash

- √ Temperature: 55°C 65°C
- √ Wash tank capacity: 100 I
- ✓ Pump: 3.5 Hp / 2600 W
- √ Wash heating element: 9000 W

Pre-rinse

- ✓ Temperature: 65°C 75°C
- √ Pre-rinse basin capacity: 15 I
- ✓ Pump: 0.2 Hp / 0.15 W
- ✓ Pre-rinse heating element: 6000 W

Rinse

√ Temperature: 80°C - 90°C





RACK CONVEYOR DISHWASHER SRC-5000

183 / 275 baskets per hour (up to 4950 plates/hour). Pre-washing + first washing + enhanced washing + double rinsing.

√ Water consumption: 480 l/h

✓ Rinse heating element: 27000 W

√ Boiler capacity: 20 I

√ Width: 3500 mm

Drag

✓ Drag motor power: 0.25 Hp / 180 W

Loading

✓ Central module total power: 52790 W

External dimensions (W x D x H)

✓ Depth: 829 mm ✓ Height: 1520 mm Net weight: 540 kg Water Intake: 3/4" Drain diameter: 1 1/2"

Please note: +3kW rinse heating element in models equipped

with steam condenser. **Crated dimensions**

Noise level (1m.): 71 dB(A)

4370 x 980 x 2000 mm

AVAILABLE MODELS

1302807	SRC-5000DCA 400/50/3N
1302805	SRC-5000DEV 400/50/3N
1302802	SRC-5000DCV 400/50/3N
1302812	SRC-5000DS8CA 400/50/3N
1302827	SRC-5000DS8CA 220/60/3
1302811	SRC-5000DS8EV 400/50/3N
1302810	SRC-5000DS8CV 400/50/3N
1302819	SRC-5000ICA 400/50/3N
1302817	SRC-5000IEV 400/50/3N
1302814	SRC-5000ICV 400/50/3N
1302825	SRC-5000IS8CA 400/50/3N
1302826	SRC-5000IS8CA 220/60/3
1302824	SRC-5000IS8EV 400/50/3N
1302822	SRC-5000IS8CV 400/50/3N
1302823	SRC-5000IS8CV 380/60/3

^{*} Ask for special versions availability

S sammic	www.sammic.com		
Food Service Equiment Manufacturer			

Polígono Basarte, 1. 20720 Azkoitia, Spain phone +34 943 15 72 36 sales@sammic.com



Project	Date
Item	Qty

Approved